



C Prox Ltd (Inc Quantek)

11 Callywhite Business Park, Callywhite Lane, Dronfield S18 2XP

+44(0)1246 417113 sales@cproxltd.com www.quantek.co.uk

Standalone Single Door Access Control Kits

Self-contained access control systems that are ideal for securing single timber and aluminium doors. Everything you need to make the system work in one box!

All kits include the following:

1 x **PSU-BB-12V-1A** Battery backup power supply

1 x **BATT2.3** Ah Battery

1 x **CP280S** Single mag lock 600lbs holding force (fire rated available on request, add **-FR** to part code)

1 x **CP28ZL** Brackets

1 x **SGREL** Touch sensor door release button (single gang size 86 x 86mm)

1 x **EDR-1N** Single pole break glass with LED, sounder & cover

5 x Proximity fobs

1 x Waterproof access control device – see details below

CPK0 choose your own keypad, reader or intercom



CPK1 includes the KPS

- Waterproof, conforms to IP66
- One relay output
- Strong anti-vandal zinc alloy powder coated housing
- Full programming from the keypad
- Admin add/delete cards for quick programming of card users
- 1000 users, supports card, PIN, or card + PIN
- Card frequency 125KHz EM
- PIN length 4-6 digits
- Backlit keys
- Pulse (adjustable) or toggle mode
- Built in light dependent resistor (LDR) for antitamper
- Pre-wired 1 metre cable
- Dimensions: 114.5 x 75 x 22mm



CPK2 includes the KPN

- Waterproof, conforms to IP66
- One relay output
- Strong anti-vandal zinc alloy powder coated housing
- Full programming from the keypad
- Admin add/delete cards for quick programming of card users
- 1000 users, supports card, PIN, or card + PIN
- Card frequency 125KHz EM
- PIN length 4-6 digits
- Backlit keys
- Pulse (adjustable) or toggle mode
- Built in light dependent resistor (LDR) for antitamper
- Pre-wired 1 metre cable
- Dimensions: 134 x 55 x 21mm



CPK3 includes the PN20

- Waterproof, conforms to IP66
- One relay output
- Strong anti-vandal zinc alloy powder coated housing
- Remote control for programming
- Admin add/delete cards for quick programming
- 2000 users
- Card frequency 125KHz EM
- PIN length 4-6 digits
- Pulse (adjustable) or toggle mode
- Built in light dependent resistor (LDR) for antitamper
- Pre-wired 0.5 metre cable
- Dimensions: 103 x 48 x 19 mm



CPK4 includes the FPN

- Optical fingerprint module
- One relay output
- Strong anti-vandal zinc alloy powder coated housing
- Remote control for programming
- Admin add/delete cards for quick programming
- 1000 users
- Card frequency 125KHz EM
- Waterproof, conforms to IP66
- Pulse (adjustable) or toggle mode
- Built in light dependent resistor (LDR) for antitamper
- Pre-wired 1 metre cable
- Dimensions: 128 x 48 x 26mm



CPK5 includes the KPFA-BT

- Bluetooth – Programmed and managed by mobile App
- Access by touch keypad, proximity, fingerprint, remote control or mobile phone.
- Set access times for individuals
- PIN user capacity: Custom: 150
Dynamic: 150
- Card user capacity: 200
- Fingerprint user capacity: 100
- View access records
- Connect to the internet with a gateway
- One relay output
- Strong anti-vandal zinc alloy powder coated housing
- Card frequency 13.56MHz
- Waterproof, conforms to IP66
- Pulse (adjustable) or toggle mode
- Terminal connections
- Dimensions: 148 x 43.5 x 22mm

