



C Prox Ltd (inc Quantek)

Unit 11 Callywhite Business Park, Callywhite Lane, Dronfield, S18 2XP

+44(0)1246 417113 sales@cproxltd.com www.quantek.co.uk

Disabled Toilet Locking System

All units incorporate Steritouch antibacterial additive, active for the lifetime of the product.

Now with Audio Warning / Confirmation and No Touch operation.

Steritouch: Unlike surface disinfectants which temporarily eliminate bacteria from surfaces, the protection is built-in so it will never wash off or wear away, protecting it for its lifetime!

The antimicrobial acrylic is non scratch, anti - reflective and non-porous which makes our products easy to clean and maintain, controlling the growth of bacteria and fungi without affecting the colour or transparency.

Our disabled toilet locking system is the system of choice due to its simple, easy to use, reliable and adaptable design. Can be simply configured to any specification. RADAR Key systems also.

Specification:

Powered by 12-24Vdc.

Switching red & blue LEDs to show engaged or vacant status.

(helping colour blind users – we strongly advise against flashing Lights)

Operation by anti-microbial No touch switches.

Switching available in a choice of styles to suit the installation.

Key-switch on all external sensors for emergency entry.

Anti-prank contact to prevent misuse.

Timed clean output for auto door activation.

NEW Optional audio message unit will give “Caution Door opening” & “Door Locked” notification on internal and external units.

The system can be configured in many ways, below are the 4 basic formats.

1) 2 sensor operation: Door unlocked, enter manually or operate sensor for assisted entry, operate internal sensor to lock the door, operate again to unlock the door with assisted exit.

2) 2 Sensor operation: Door Locked, operate sensor for assisted entry, operate internal sensor to lock the door, operate again to unlock the door with assisted exit.

3) 3 sensor operation: Door unlocked, enter manually or operate sensor for assisted entry, operate internal sensor to lock the door, operate again to unlock door, exit manually or operate internal door assist sensor to gain assisted exit.

4) Secure access: Door locked, a proximity token/card is required to gain manual or assisted entry, operate internal sensor to lock the door, operate again to unlock door, exit manually or with assisted exit.



Single Gang



Architrave



Round



Square



RADAR Key Option
As fitted to LNER
train stations